

SN 09/410748




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A61B 19/00, A61M 35/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/29249 (43) International Publication Date: 17 June 1999 (17.06.99)</p>
<p>(21) International Application Number: PCT/SE98/02115 (22) International Filing Date: 20 November 1998 (20.11.98) (30) Priority Data: 9704261-8 20 November 1997 (20.11.97) SE (71) Applicant (for all designated States except US): CARDIA INNOVATION AB [SE/SE]; Engelbrektsgatan 19, S-114 32 Stockholm (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): VAN DER LINDEN, Jan [SE/SE]; Lillskogsvägen 22, S-133 34 Saltsjöbaden (SE). (74) Agents: BERGLUND, Stefan et al.; Bjerkéns Patentbyrå KB, Östermalmsgatan 58, S-114 50 Stockholm (SE).</p>	<p>(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Swedish).</p>	

(54) Title: A METHOD AND A DEVICE FOR PRODUCING AN ATMOSPHERE IN A REGION, AND USE OF CARBON DIOXIDE FOR THE MANUFACTURE OF A MEDICAMENT



(57) Abstract

The invention refers to a method and a device for creating an atmosphere in an area, which adjoins an outwardly open, inner portion of the body of a human being or an animal. By the aid of a gas supply member (1) a gas from a gas source (5) is supplied to the area. The supplied gas comprises a substantial amount of carbon dioxide, which in relation to oxygen and nitrogen has a high solubility in tissue and which prevents a bacteria growth in the area.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

A method and a device for creating an atmosphere in an area and a use of carbon dioxide for the manufacture of a medicament

10 THE BACKGROUND OF THE INVENTION AND PRIOR ART

The present invention refers to a method for creating an atmosphere in an area which adjoins an outwardly open, inner portion of the body of a human being or an animal, comprising the
15 step of supplying a gas to the area which gas forms a main component in said atmosphere. The invention also refers to a device for creating an atmosphere in an area which adjoins an outwardly open, inner portion of the body of a human being or an animal, which device comprises a gas supply member which is
20 connectable to a gas source.

When an outwardly open portion arises on the body of a human being or an animal, the risk for infections due to bacteria or any other micro-organisms increases, which micro-organisms may
25 easily penetrate the body because the protective skin is removed. Such open portions arise in connection with operations and other surgery operations and in the case of open wounds, which may have been caused by different injuries, accidents or diseases. In order to reduce this risk of infection one attempts, at least at
30 hospitals, to keep the surrounding atmosphere and the skin as sterile as possible by filtering and cleaning, respectively, and by the use of different types of disinfectant. Of course it is important to close as quick as possible such open portions to prevent the penetration of bacteria.

35

Furthermore, in connection with operations tissues and vessels are exposed to air, the main components of which, i.e. nitrogen and

oxygen, hardly dissolve in tissue. This results in an activation of a plurality of so-called cascade systems, inter alia within coagulation. Within vessel and heart surgery, the situation is more complicated by the fact that due to the opening of the vessels and the heart one
5 can both actively and passively introduce air into the cavities of the vessels and the heart. Thereafter, it is very difficult to remove completely the air from the vessels and the heart merely by blood filling without air bubbles being further transported with the
10 bloodstream, due to the fact that air mixed with blood gives bubbles similar to a foam. When the bubbles of air are transported with the bloodstream to the capillaries, the bubbles remain in the capillaries during some minutes, whereafter they are slowly absorbed or slowly pass the capillaries. The inside of the vessels, including the inside
15 of the capillaries, is covered with endothelial, which is very depending on oxygen, i.e. depending on the oxygen bond in the blood, and a remaining air bubble in a small vessel or capillary results in an endothelium injury. Also when the bubble has been absorbed or transported further this activates and results in the injured endothelium wall being covered by white blood cells which
20 in turn already can be ready to attach to the injured endothelium due to the so called operation trauma and/or the exposing to foreign material through for example the use of a heart-lung-machine. The result is an embolisation, i.e. a blocking of the vessel and the capillary of firstly the air bubble, which remains in the vessel during
25 in the range of minutes, and secondly of white blood cells, which remain during a long time because of the following reaction between the injured endothelium and active white blood cells. Thereby, the area which is supported by the vessel and the capillary gets no blood support, whereby in particular oxygen
30 depending tissue, especially the brain, is injured.

SUMMARY OF THE INVENTION

35 The object of the present invention is to create a desired atmosphere in connection with outwardly open body portions, such as in connection with surgery operations. In particular, according to a first aspect of the invention, it is aimed at the prevention of

bacteria growth in such portions and according to a second aspect of the invention, it is aimed at a reduction of the problem of embolisation in connection with surgery operations, in particular vessel and heart surgery.

5

This object is obtained by the device initially defined and characterized in that said gas comprises a substantial amount of carbon dioxide.

- 10 Carbon dioxide has bacteriostatic/bactericidal properties and by creating an atmosphere of carbon dioxide in an area, which surrounds an open portion of the body, one may effectively prevent a bacterial growth in the open portion, for example a wound or a surgical cut. Moreover, the supplied carbon dioxide may be
- 15 substantially completely sterile, i.e. the supplied gas comprises no micro-organisms or bacteria, and in this way bacteria or micro-organisms which exist in the surrounding air are prevented from reaching said area. The bacteria or micro-organisms which exist in the area or which for some reason would manage to penetrate the
- 20 area can however not propagate themselves. Furthermore, one may by the supply of the carbon dioxide gas prevent the entrance of the surrounding air to an open area of the body in connection with an operation or a surgery operation. Consequently, air may not penetrate the bloodstream and cause the above discussed air embolisation. Carbon dioxide, which in relation to the main
- 25 components in air, i.e. oxygen and nitrogen, has a high solubility in tissue, may be permitted to penetrate the open body portion because carbon dioxide is not going to create bubbles but rapidly be resorbed in the tissue and in this way embolisation and thereby
- 30 blocking of small vessels and capillaries, may be avoided. Consequently, the carbon dioxide does not remain as bubbles in the blood vessels and will therefore not prevent the bloodstream in the same way as common air. Moreover, carbon dioxide is more heavy than air and therefore one may in a simple way create an
- 35 atmosphere free from air in said area, since the more heavy carbon dioxide will pass downwardly into the open body portion and force away the air which exists down in this open portion. Furthermore,

the carbon dioxide is substantially inert with regard to living organisms at least when it appears in moderate quantities.

5 According to a further embodiment of the invention, said gas is supplied to the area in a substantially continuous flow. In this way, it is possible to guarantee an atmosphere which is free from air in said area although some of the supplied gas leaves the area.

10 According to a further embodiment of the invention, said gas is supplied to the area in a substantially laminar flow. By such a laminar flow, it is possible to supply said gas in a controlled way and thereby it is also possible to avoid or at least substantially reduce the presence of turbulence in the area, which otherwise might result in the suction of air from the surrounding atmosphere
15 into the area.

According to a further embodiment of the invention, the area is shielded off from the surrounding atmosphere in such a way that the supplied gas is kept within the area. By such a shielding off, the
20 surrounding air is also prevented from penetrating the area, and consequently the maintaining of the atmosphere free from air is facilitated.

25 According to a further embodiment of the invention, a stream of said gas is supplied in a direction towards a part of said inner body portion. At least in some cases such a simple performing of the method, with only one or a few flow streams of said gas, is enough for keeping, within a limited area, the atmosphere substantially free
30 from air.

According to a further embodiment of the invention, said gas is humidified before it is supplied to the area. In such a way, one may in an effective way reduce the evaporation from the open portion and consequently prevent dehydration.
35

The object is also obtained by the device initially defined and characterized by a gas source which comprises a gas with a

substantial amount carbon dioxide and in that the gas supply member is arranged to supply said gas to said area in such a way that the carbon dioxide forms a main component in said atmosphere.

5

Preferred embodiments of the device are defined in the depending claims 7 – 12. Thereby, the gas supply member may permit the supply of said gas to the area in a substantially continuous flow. The gas supply member may also comprise a nozzle which is
10 arranged to supply said gas in a substantially laminar flow to the area.

The object is also obtained by a use of carbon dioxide for the manufacture of a medicament to be supplied to an outwardly open
15 inner portion of the body of a human being or an animal in order to create an atmosphere, which prevents growth of micro-organisms comprising bacteria and virus in said area. Furthermore, the object is obtained by a use of carbon dioxide for the manufacture of a medicament to be supplied to an outwardly open inner portion of the
20 body of a human being or an animal in order to create an atmosphere, which prevents penetration of air into said area.

BRIEF DESCRIPTION OF THE DRAWINGS

25 The present invention is now to be explained more closely by means of an embodiment and with reference to the attached drawings, in which

- 30 Fig 1 discloses a schematic view of a device according to a first embodiment of the invention.
- Fig 2 discloses a cross-sectional view through one part of the device in Fig 1.
- Fig 3 discloses a schematic view of a device according to a second embodiment of the invention.
- 35 Fig 4 discloses a cross-sectional view through a part of the device in Fig 2.

Fig 5 discloses a schematic view of a device according to a third embodiment of the invention.

Fig 6 discloses a schematic view of a device according to a fourth embodiment of the invention.

5

DETAILED DESCRIPTION OF DIFFERENT EMBODIMENTS OF THE INVENTION

10 With reference to Figs 1 and 2, a device is shown for supplying a gas to an area which surrounds and adjoins an open, inner portion of a human being, which portion is open at least during a limited time period. Such an open portion is formed in connection with surgery operations. In connection with, for example, heart operations a substantial part of the inside of the thorax is
15 uncovered so that this part in normal cases has direct contact with the surrounding atmosphere, i.e. with air and consequently it is exposed to attack from the bacteria and micro-organisms which exist in the environment.

20 The device comprises a gas supply member 1 which is designed as a hose-like, tubular body 2, which extends in a wholly or partially closed ring and is intended to be arranged around an open portion P of a patient who is subjected to a surgery operation. The tubular body 2 forms an annular channel 3 and comprises a number of
25 openings 4, which face the centre of the ring and which form nozzles for outflowing gas. The annular channel 3 is connected to a gas source in the shape of a gas container 5 through a gas conduit 6. Consequently, gas from the gas container 5 may be supplied to the annular channel 3 through the gas conduit 6 and be blown out
30 towards the centre of the gas supply member 1 through the openings 4. The gas conduit 6 comprises a valve member 7 by which the gas supply to the annular channel 3 is adjustable. In the example shown, the valve member 7 is controlled with the aid of a control member 8 connected to the valve member 7. The control
35 member 8 may in turn be connected to a gas-sensing member 9, which is arranged to sense the concentration of the supplied gas or of the air in the area in question. With the aid of such a sensing, the

gas supplied to the area may be controlled in, for example, such a way that if an increased air concentration is determined, the gas supplied is also increased or if the concentration of air in the area exceeds a predetermined level, the gas supply is increased.

5

The openings 4 are in the example disclosed in Fig 1 designed as slit-shaped openings 4, which extend in the direction of the circumference of the body 2. Also other shapes of the openings 4 are possible, for example they may be formed by substantially circular or oval apertures. Fig 2 shows a part of the tubular body 2 and how the openings 4 may be shaped. Thereby, it is seen that the openings 4 have an extension also in the out-blow-direction of the gas and that the length of this extension exceeds the wall thickness of the hose-like body 2 forming the annular channel 3. Thereby, it is possible to direct the gas flow in a desired direction towards an open portion of the body of the patient. By this embodiment of the openings 4, it is also possible to achieve a substantially laminar gas flow. It is to be noted that within the scope of the invention, it is also possible to let simple apertures in the wall of the hose-like body 2 form the nozzles for the gas supply.

20

The gas supply member 1 may be produced from a number of different materials. However, it is advantageously produced from some flexible material, such as rubber or plastic. In this way, the gas supply member 1 may adjust itself to the contour of the body of the patient to whom it is placed. Since the hose-like, tubular body 2 forms a closed loop and abuts the body of the patient, it will also, at least to some extent, prevent the supplied gas from exiting the area, which the gas supply member 1 encloses.

30

With reference to Figs 3 and 4, a second embodiment of the gas supply member according to the invention is disclosed. It is to be noted here that components with substantially the same function have been provided with the same reference signs in the different embodiments disclosed. The second embodiment differs from the first embodiment with regard to the design of the gas supply member 1, which comprises a cylinder-shaped shield member 10,

35

which is applied on the body of the patient and attached with the aid of a belt member 11 or the like, which extends around the patient. Furthermore, as is disclosed in Fig 4, the gas supply member 1 comprises an annular channel 3, which is defined by a wall member 12, arranged at the inner side of the shield member 10. The wall member 12 comprises a number of elongated openings 4, which extend in the direction of the circumference of the shield member 10. Each opening 4 is defined by two lamella or guide vanes 13, which together with the openings 4 form a nozzle, by which the supplied gas may be directed in a desired direction towards an open portion of the body of the patient. With the aid of these lamella 13, it is also possible to achieve a substantially laminar gas flow. Also in this case, the gas supply member 1 may be produced from a number of different materials. Advantageously, at least the lower portion of the gas supply member 1, which abuts the patient, is produced from some flexible material, such as rubber or plastic. In this way, the gas supply member 1 may adapt itself to the contour of the body of the patient to whom it is attached. Due to the relatively high shield member 10, which may be applied in such a way that it extends upwardly from the body of the patient, the supplied gas will be prevented from exiting the area, which the gas supply member 1 encloses. It is to be noted that also in the second embodiment, the openings 4 can have many different shapes, such as for example a plurality of small round or oval apertures with or without lamella or guide vanes for guiding the gas flow.

Fig 5 discloses a third embodiment, wherein the gas supply member 1 only comprises a gas conduit 6 with a funnel-shaped, expansive nozzle 14. The nozzle 14 comprises, in the example disclosed, two guide vanes 15, which contribute to the possibility of directing the gas flow in a desired direction towards an open portion of the body of the patient. With the disclosed, expanding nozzle 14, it is also possible to achieve a substantially laminar gas flow.

Fig 6 discloses a fourth embodiment, which is similar to but less complicated than the third embodiment. In the fourth embodiment, the gas supply member comprises only a flexible hose 6, which is

provided with a number of small apertures 16, through which the supplied gas is discharged. This embodiment is suitable in particular for application in cavities in the body of the patient.

- 5 The device may, but not necessarily, comprise a humidifying member 17, see Figs 1, 3, 5 and 6, by which the supplied gas may be humidified. The humidifying member 17 may be of a known type per se and provided to humidify the gas with water or water steam, for example a physiological sodium chloride solution.

10

- According to a preferred embodiment of the invention, the supplied gas from the gas container 5 is mainly carbon dioxide, which has a high solubility in body tissue, which is substantially bacteriostatic or inert with regard to living organisms and which furthermore is heavier than air. The gas may be supplied by the aid of a pressure, above atmospheric, in the gas container 5 or by the aid of a pump (not disclosed). To maintain a laminar gas flow, the flow speed has to be relatively low.

15

- 20 It is also possible to cool the gas, which is supplied the open portion P to a temperature level, which is somewhat lower than the temperature of the surrounding air. Such a cooling may take place both if the gas is humidified and if it is not humidified. The cooling has the advantage that the supplied gas, due to its lower temperature, obtains a higher density and consequently becomes heavier. In such a way, the gas will easier penetrate the open portion P, and consequently, more easily force the air away. Furthermore, the carbon dioxide, which has a relatively low temperature, will further restrain a possible growth of bacteria or other micro-organisms. Such a cooling may be achieved in many different ways, for example with a heat exchanger, which is arranged in connection with the gas conduit 6.

25

30

- The present invention is not limited to the above-disclosed embodiments but can be varied and be modified within the scope of the following patent claims. For example, it is to be noted that the channel 3 disclosed in Figs 1 - 4 need not to extend in a closed,

35

- annular loop but can extend along only a part of a round. It is also to be noted that it within the scope of the invention is possible to form a completely closed area around the open portion and that said gas is supplied to this enclosed atmosphere and the air is removed before, after or during the gas supply. The size of this area may be varied for different applications and it is also possible to let this area be big enough to include completely or partly the individuals performing the surgery operation within the area.
- 5
- 10 The defined outwardly open, inner portion in this present application may have an arbitrary size and comprises not only large operation fields but also smaller passages through the skin, for example smaller wounds. Consequently, the invention is also applicable to the case that a gas-formed medium is permitted to flow towards
- 15 such a smaller passage in order to force away the blood, which flow out from the passage. In such a way, one may visualise the operation field and thereby facilitate the surgery operation at the same time as an atmosphere free from bacteria is created.

Claims

1. A method for creating an atmosphere in an area which adjoins an outwardly open, inner portion of the body of a human being or an animal, comprising the step of supplying a gas to the area which gas forms a main component in said atmosphere, characterized in that said gas comprises a substantial amount of carbon dioxide.
2. A method according to claim 1, characterized in that said gas is supplied to the area in a substantially continuous flow.
3. A method according to any of the claims 1 and 2, characterized in that said gas is supplied to the area in a substantially laminar flow.
4. A method according to any one of the preceding claims, characterized in that the area is shielded off from the surrounding atmosphere in such a way that the supplied gas is kept within the area.
5. A method according to any one of the preceding claims, characterized in that a stream of said gas is supplied in a direction towards a part of said inner body portion.
6. A method according to any one of the preceding claims, characterized in that said gas is humidified before it is supplied to the area.
7. A device which is provided to create an atmosphere in a area, which adjoins an outwardly open, inner portion (P) of the body of a human being or an animal, which device comprises a gas supply member (1), which is connectable to a gas source (5), characterized in that the gas source (5) comprises a gas with a substantial amount of carbon dioxide and that the gas supply member (1) is arranged to supply said gas to said area in such a way that the carbon dioxide forms a main component in said atmosphere.

8. A method according to claim 7, characterized in that the gas supply member (1) is arranged to enable the supply of said gas in a substantially continuous flow to the area.
- 5 9. A device according to any of the claims 7 and 8, characterized in that the gas supply member (1) comprises a nozzle (4, 13), which is provided to supply said gas in a substantially laminar flow to the area.
- 10 10. A device according to any of the claims 7 – 9, characterized in that it comprises a shield member (10), which is provided to be arranged around the area and to prevent the supplied gas from exiting the area.
- 15 11. A device according to any of the claims 7 – 10, characterized in that the gas supply member (1) comprises several nozzle openings (4), which are arranged to direct a flow of said gas towards the centre of the area.
- 20 12. A device according to claim 11, characterized in that the nozzle openings (4) are provided in a ring-shaped configuration, which is arranged to surround the area.
- 25 13. A device according to any one of the claims 7 – 12, characterized in that the gas supply member (1) comprises a nozzle (4), which is arranged to supply a stream of said gas and which is adjustable in a direction towards a part of said inner body portion.
- 30 14. A device according to any one of the claims 7 – 13, characterized by a humidifying member (7), which is provided to humidify said gas.
- 35 15. A use of carbon dioxide for the manufacture of a medicament to be supplied to an outwardly open inner portion of the body of a human being or an animal in order to create an atmosphere, which prevents growth of micro-organisms comprising bacteria and virus in said area.

16. A use of carbon dioxide for the manufacture of a medicament to be supplied to an outwardly open inner portion of the body of a human being or an animal in order to create an atmosphere, which
5 prevents penetration of air into said area.




Fig 2








Fig 3Fig 4

Fig 5Fig 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 98/02115

A. CLASSIFICATION OF SUBJECT MATTER				
IPC6: A61B 19/00, A61M 35/00 According to International Patent Classification (IPC) or to both national classification and IPC				
B. FIELDS SEARCHED				
Minimum documentation searched (classification system followed by classification symbols)				
IPC6: A61B, A61M, A61G, A61H				
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched				
SE,DK,FI,NO classes as above				
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)				
C. DOCUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
X	WO 9726034 A1 (HEARTPORT, INC), 24 July 1997 (24.07.97), page 4, line 8 - line 38 --	7-16		
X	WO 9639942 A1 (HEARTPORT, INC.), 19 December 1996 (19.12.96), page 46, line 20 - line 32 --	7-16		
X	FR 2656218 A1 (COMPAGNIE FRANÇAISE DES PRODUITS OXYGENES), 28 June 1991 (28.06.91), page 2 - page 3 --	7-16		
X	DE 2646710 A1 (NOURI, ZIAD), 20 April 1978 (20.04.78), page 7 - page 8, figure 4 -- -----	7-16		
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.				
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top; border: none;"> <p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </td> <td style="width: 50%; vertical-align: top; border: none;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p> </td> </tr> </table>			<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>			
Date of the actual completion of the international search		Date of mailing of the international search report		
28 April 1999		19-05-1999		
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. + 46 8 666 02 86		Authorized officer Anette Hall Telephone No. + 46 8 782 25 00		

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE98/02115

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 1-6
because they relate to subject matter not required to be searched by this Authority, namely:

A method of treatment of the human or animal body by surgery or therapy (Article 17(2)(a)(i) and Rule 39.1(iv)).

2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 98/02115

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	9726034	A1	24/07/97	AU	1749897 A	11/08/97
				US	5849005 A	15/12/98
WO	9639942	A1	19/12/96	AU	5951996 A	30/12/96
				CA	2239907 A	19/12/96
				EP	0836423 A	22/04/98
				US	5849005 A	15/12/98
FR	2656218	A1	28/06/91	NONE		
DE	2646710	A1	20/04/78	NONE		

THIS PAGE BLANK (USPTO)